



参数表 PARAMETER LIST

电气特性 Electric characteristic	AC250V/16A 100000cycles ; AC125V/15A 100000cycles ;
接触电阻 Contact resistance	≤50mΩ
触点形式 Contact model	常闭
产品标识 Product	KST-A安装板定位;KST-B 非安装板定位; KST-C 安装结构是桥式形状; KST-D 压板安装; KST-R 温控自带电阻补偿 KST-A assembly board fixture; KST-B none assembly board fixture; KST-Cbridge type assembly structure; KST-D push board assembly; KST-R thermostat with resistance offset
使用环境极限温度 Lowest ambient temp	动作温度+50℃，且最高不能超过300℃ 1分钟 Action temp 50℃,not high to 300℃
温度范围 temp range marking	0-250℃
温度公差 Temp intorance	±5℃ (≤100℃) ; ±5%℃ (> 100℃) 或依客户整机匹配 ±5℃ (≤100℃) ; ±5%℃ (> 100℃) according to client equipment to match
认证 Certification	UL、TUV、CQC

应用 APPLICATION

- (1) 电熨斗，电烤箱，油炸锅
Electric Iron , Electric Oven , Oil Fryer
- (2) 暖奶器，热波炉，光波炉，电压力锅，电饭煲
Milk Heater , Heat Wave Furnace , Light Wave Furnace, Electric Pressure Cooker , Electric Rice Cooke
- (3) 电饼铛、暖风机、BBQ等
Electric Baking Pan , Heater , BBQ , Etc

储存及安装注意事项 STORAGE AND INSTALLATION PRECAUTIONS

- (1) 产品应在相对湿度小于90%，环境温度40℃以下通风、洁净、干燥、无腐蚀性气体的场所中存放
The product should be stored in a ventilated, clean, dry and non-corrosive place with relative humidity less than 90% and ambient temperature below 40%.
- (2) 为确保感温效果，并在器具感温表面涂上导热膏
In order to ensure the temperature effect, and heat the paste on the surface of the instrument.
- (3) 安装时温控器的陶瓷、双金属片等物理状况应不受外力的作用而保持原样
When installing, the physical state of the ceramic and bimetal of the thermostat shall remain unchanged without external force.